

- ◆ Combines VHF (50-220 MHz) to UHF (400-960 MHz)
- ◆ **Models for Outdoor Environments**
- ◆ High Input Isolation
- ◆ High Average Power
- ◆ Minimal RF Insertion Loss
- ◆ Rugged, High Reliability, RoHS
- ◆ Low Passive IM., PIM
- ◆ Low Cost Design




Model Number	Connectors (female)	Weight, nom. lb (kg)
<b>BK-04D</b>	7-16 mm	2.2 (1.0)
<b>BK-04N</b>	N	1.9 (0.8)
Add 'P' to Model Number for Outdoor Use		

	Pass Bands, MHz	Input Isolation	Pass Band Loss	Power Rating Avg, peak
Input P1	50 - 220	>50 dB	<0.8 dB	50W., 3 kW
Input P2	400 - 960	>50 dB	<0.8 dB	100W., 3 kW

Input Return Loss:	>18 dB
Impedance:	50Ω nominal
Intermod. (PIM):	<-153 dBc 2 x +43dBm tones
Environment:	-35 to +65°C
Housing Finish:	
Indoor/IP64:	Standard model Passivated Al.
Outdoor/IP67:	Painted Add P to Model No.
Connectors:	Triplate

Microlab Model BK-04 series is a Diplexer which allows combination and separation of signals in the 50 - 220 MHz and 400 - 960 MHz wireless bands. To minimize band inter-reaction, the inputs are well isolated and have minimal insertion loss over their respective frequency bands. The Diplexer is designed using passive, proprietary techniques for low loss, low PIM and high reliability

For use in outdoor environments add the suffix 'P' to Model No. (e.g. BK-04NP).



Note: Specifications are subject to change without prior notification.

22JUN2016